

IN THE CLAIMS:

Amend Claims 3-8 10, 11, 14, and 15 as follows and add

Claims 16-20:

1. (Original) Condenser for an air-based climate control system, having an inlet and an outlet for the air to be cooled, an inlet and an outlet for the cool air, a heat exchange unit for heat transfer between the air to be cooled and the cool air, a bypass that circumvents the cool-air side of the heat exchange unit at least within a certain area, and a hot-air inlet on the cool-air side by means of which hot-air can be fed into the condenser,

characterized in that

the hot-air inlet is positioned in such a way that the hot air essentially flows in a partial area on the cool-air side of the condenser inlet and that the bypass inlet is positioned in the partial area downstream of the hot-air inlet.

2. (Original) Condenser according to Claim 1, characterized in that the bypass is positioned in the edge area of the condenser or in the center or in an area between these positions.

3. (Currently amended) Condenser according to Claim 1 ~~or~~ 2, characterized in that the bypass is an integral component of the condenser.

4. (Currently amended) Condenser according to Claim one ~~one of Claims 1 to 3~~, characterized in that the hot-air inlet and the bypass inlet are oriented toward one another in such a way that the hot-air stream is fed entirely through the bypass.

5. (Currently amended) Condenser according to Claim one of Claims 1 to 3, characterized in that the hot-air inlet and the bypass inlet are oriented toward one another in such a way that the hot-air stream is fed predominantly through the bypass.

6. (Currently amended) Condenser according to Claim one of Claims 1 to 5, characterized in that the bypass is positioned in the edge area of the heat exchange unit and that an area, through which the air to be cooled can flow, is positioned between the outer wall of the heat exchange unit and the wall of the bypass.

7. (Currently amended) Condenser according to Claim one of Claims 1 to 6, characterized in that two or more bypasses are provided that are each positioned in the edge area of the condenser.

8. (Currently amended) Condenser according to Claim one of Claims 1 to 6, characterized in that one more than one valve is provided, by means of which the volume flow of the hot air fed to the bypass or bypasses can be modified.

9. (Original) Condenser according to Claim 8, characterized in that the valve or valves are integrated into the heat exchange unit.

10. (Currently amended) Condenser according to Claim one of Claims 1 to 9, characterized in that a water eliminator is provided that is integrated into the outlet of the cool air or of the air to be cooled.

11. (Currently amended) Condenser according to Claim one of Claims 1 to 10, characterized in that the heat exchange unit is designed in any desired manner, in particular, as a cross flow, counterflow, or uniflow heat exchanger.

12. (Original) Air-based climate control system, especially for aircraft, having at least one turbine for decomposition and cooling of air to be fed into the passenger cabin and having a condenser with a heat exchange unit, the inlet of which on the cool-air side is connected with the turbine outlet, and having an admixture conduit by means of which hot-air can be mixed into the air to be fed into the passenger cabin,

characterized in that

the admixture conduit feeds in downstream of the inlet on the cool-air side of the heat exchange unit.

13. (Original) Climate control system according to Claim 12, characterized in that the admixture conduit feeds into the outlet area of the heat exchange unit in the condenser.

14. (Currently amended) Climate control system according to Claim ~~Claims 12 or 13~~, characterized in that a ram air canal is provided in which one or more heat exchangers are positioned, through the cold air side of which ram air or ambient air flows, and the hot-air side of which is connected with a hot-air conduit that is connected with the admixture conduit in such a way that the admixture conduit is supplied with hot air from the hot-air conduit.

15. (Currently amended) Climate control system ~~according to one of Claims 12 to 14~~, characterized in that the comprising a condenser is designed according to Claim ~~one of Claims 1 to 14~~ and the an admixture conduit is formed by a the bypass of the condenser.

16. (New) Condenser according to Claim 2, characterized in that the bypass is an integral component of the condenser.

17. (New) Condenser according to Claim 2, characterized in that the hot-air inlet and the bypass inlet are oriented toward one another in such a way that the hot-air stream is fed entirely through the bypass.

18. (New) Condenser according to Claim 3, characterized in that the hot-air inlet and the bypass inlet are oriented toward one another in such a way that the hot-air stream is fed entirely through the bypass.

19. (New) Condenser according to Claim 2, characterized in that the hot-air inlet and the bypass inlet are oriented toward one another in such a way that the hot-air stream is fed predominantly through the bypass.

20. (New) Condenser according to Claim 2, characterized in that the hot-air inlet and the bypass inlet are oriented toward one another in such a way that the hot-air stream is fed predominantly through the bypass.